

Input Values			inch/hour	feet/da	ay
0.2580	\boldsymbol{R}	Recharge (infiltration) rate (feet/day)	0.6	7	1.33
0.080	Sy	Specific yield, Sy (dimensionless, between 0 and 1)			
5.40	K	Horizontal hydraulic conductivity, Kh (feet/day)*	2.0	2.00 4.00	
98.420	x	1/2 length of basin (x direction, in feet)			In the repor (USGS SIR 20
20.670	У	1/2 width of basin (y direction, in feet)	hours	days	(ft/d) is assu
1.000	t	duration of infiltration period (days)	3	6	1.50 hydraulic co
5.000	hi(0)	initial thickness of saturated zone (feet)			

7.339 h(max) 2.339 Δh(max) maximum thickness of saturated zone (beneath center of basin at end of infiltration period) maximum groundwater mounding (beneath center of basin at end of infiltration period)

Ground- Distance from water center of basin Mounding, in x direction, in


feet feet

	0	2.339
ı	20	2.338
	40	2.329
	50	2.313
	60	2.275
	70	2.192
	80	2.022
	90	1.695
	100	1.086

120



Re-Calculate Now



Disclaimer

0.243

This spreadsheet solving the Hantush (1967) equation for ground-water mounding beneath an infiltration basin is made available to the general public as a convenience for those wishing to replicate values documented in the USGS Scientific Investigations Report 2010-5102 "Groundwater mounding beneath hypothetical stormwater infiltration basins" or to calculate values based on user-specified site conditions. Any changes made to the spreadsheet (other than values identified as user-specified) after transmission from the USGS could have unintended, undesirable consequences. These consequences could include, but may not be limited to: erroneous output, numerical instabilities, and violations of underlying assumptions that are inherent in results presented in the accompanying USGS published report. The USGS assumes no responsibility for the consequences of any changes made to the spreadsheet. If changes are made to the spreadsheet, the user is responsible for documenting the changes and justifying the results and conclusions.

Recharge/Infiltration Rate (ft/day) = [Required Recharge Volume (cft)/Bottom Recharge System (sft)]/Duration (day)

Required Recharge Volume 2,099 cft

Bottom Recharge System 8,137 sft

Duration 1 day

Recharge/Infiltration Rate 0.2580 ft/day

Horizontal Hydraulic Conductivity (ft/day) = [Rawls Rate (in/hr) * (1ft/12in) * (24hr/1day)] * 10

Rawls Rate (silt loam) 0.27 in/hr

Horizontal Hydraulic Conductivity 5.40 ft/day

Elevation	Surface	Storage
(feet)	(sq-ft)	(cubic-feet)
6.5	8,137	0
6.55	8,137	350
6.6	8,137	700
6.65	8,137	1,050
6.7	8,137	1,400
6.75	8,137	1,750
6.8	8,137	2,099
6.85	8,137	2,449
6.9	8,137	2,799
6.95	8,137	3,149
7	8,137	3,499
7.05	8,137	3,849
7.1	8,137	4,199
7.15	8,137	4,549
7.2	8,137	4,899
7.25	8,137	5,249
7.3	8,137	5,599
7.35	8,137	5,948
7.4	8,137	6,298
7.45	8,137	6,648
7.5	8,137	6,998
7.55	8,137	7,348
7.6	8,137	7,698
7.65	8,137	8,048
7.7	8,137	8,398
7.75	8,137	8,748
7.8	8,137	9,098
7.85	8,137	9,447
7.9	8,137	9,797
7.95	8,137	10,147
8	8,137	10,497
8.05	8,137	10,847
8.1	8,137	11,197
8.15	8,137	11,547
8.2	8,137	11,897
8.25	8,137	12,247
8.3	8,137	12,597
8.35	8,137	12,947
8.4	8,137	13,296
8.45	8,137	13,646
8.5	8,137	13,996
8.55	8,137	14,346
8.6	8,137	14,696
8.65	8,137	15,046
8.7	8,137	15,396
8.75	8,137	15,746
8.8	8,137	16,096
8.85	8,137	16,446
8.9	8,137	16,796
8.95	8,137	17,145
9	8,137	17,495
-	-,	,